

List of Compatible Device Models

Logo Transfer Software

- As of April 2022 -

In using this software, bear in mind that the items whose settings must be selected for the projectors and the functions that can be used may differ from one projector model to another. While referring to the table below, check out that projector models are compatible with the software before using them.

List of models

PT-D10000	14	PT-DX610	12
PT-D12000	11	PT-DX800	12
PT-D4000	15	PT-DX810	12
PT-D5000	12	PT-DX820	8
PT-D5700	15	PT-DZ10K	8
PT-D6000	12	PT-DZ110XE	12
PT-DS100XE	12	PT-DZ12000	11
PT-DS12K	8	PT-DZ13K	8
PT-DS20K	8	PT-DZ16K	8
PT-DS20K2	8	PT-DZ16K2	8
PT-DS8500	12	PT-DZ21K	8
PT-DW100	11	PT-DZ21K2	8
PT-DW10000	14	PT-DZ570	13
PT-DW105XEA	12	PT-DZ6700	12
PT-DW11K	8	PT-DZ6710	12
PT-DW17K	8	PT-DZ680	12
PT-DW17K2	8	PT-DZ770	12
PT-DW5100	15	PT-DZ780	8
PT-DW530	13	PT-DZ870	8
PT-DW6300	12	PT-DZ8700	12
PT-DW640	12	PT-EW530	20
PT-DW730	12	PT-EW540	18
PT-DW740	12	PT-EW550	19
PT-DW750	8	PT-EW551	19
PT-DW830	8	PT-EW630	20
PT-DW8300	12	PT-EW640	18
PT-DW90XE	12	PT-EW650	19
PT-DX100	8	PT-EW651	19
PT-DX500	13	PT-EW730	18

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-EX12K	21	PT-LZ370	29
PT-EX16K	21	PT-MW530	8
PT-EX500	20	PT-MW630	8
PT-EX510	18	PT-MW730	8
PT-EX520	19	PT-MZ10K	8
PT-EX521	19	PT-MZ13K	8
PT-EX600	20	PT-MZ16K	8
PT-EX610	18	PT-MZ570	8
PT-EX620	19	PT-MZ670	8
PT-EX621	19	PT-MZ680	8
PT-EX800	18	PT-MZ770	8
PT-EZ57	19	PT-MZ780	8
PT-EZ570	20	PT-MZ880	8
PT-EZ580	18	PT-RCQ10	7
PT-EZ590	19	PT-RCQ80	7
PT-EZ591	19	PT-RQ13K	8
PT-EZ770	18	PT-RQ22K	8
PT-FRQ50	6	PT-RQ32K	8
PT-FRQ60	6	PT-RQ35K	5
PT-FRZ50	8	PT-RQ50K	4
PT-FRZ55	8	PT-RS11K	8
PT-FRZ60	8	PT-RS20K	8
PT-FW430	27	PT-RS30K	8
PT-FW530	19	PT-RW330	10
PT-FX400	27	PT-RW430	10
PT-FX500	19	PT-RW620	8
PT-FZ570	19	PT-RW630	8
PT-LB1	31	PT-RW730	8
PT-LB1V	31	PT-RW930	8
PT-LB2	31	PT-RX110	8
PT-LB2V	31	PT-RZ120	8
PT-LB3	31	PT-RZ12K	8
PT-LB306	17	PT-RZ16K	8
PT-LB356	16	PT-RZ21K	8
PT-LB386	16	PT-RZ31K	8
PT-LB426	16	PT-RZ34K	5
PT-LB75V	32	PT-RZ370	10
PT-LB78V	32	PT-RZ470	10
PT-LB90	32	PT-RZ475	10
PT-LB90NT	31	PT-RZ570	8
PT-LW25H	30	PT-RZ575	8
PT-LW336	16	PT-RZ660	8
PT-LW376	16	PT-RZ670	8
PT-LX22	30	PT-RZ690	8
PT-LX26	30	PT-RZ770	8
PT-LX26H	30	PT-RZ790	8
PT-LX30H	30	PT-RZ870	8

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-RZ890	8	PT-VX420	23
PT-RZ970	8	PT-VX421	23
PT-RZ990	8	PT-VX425N	23
PT-ST10	31	PT-VX430	23
PT-SW280A	28	PT-VX45	24
PT-SX300A	28	PT-VX46	23
PT-SX320A	28	PT-VX50	23
PT-TW230	30	PT-VX500	24
PT-TW231R	30	PT-VX501	24
PT-TW380	16	PT-VX505N	24
PT-TW381R	16	PT-VX51	22
PT-TX350	16	PT-VX510	24
PT-TX440	16	PT-VX60	23
PT-VMW50	19	PT-VX600	23
PT-VMW51	19	PT-VX605N	23
PT-VMW60	19	PT-VX61	22
PT-VMW61	19	PT-VX610	22
PT-VMZ40	19	PT-VX615N	22
PT-VMZ41	19	PT-VZ470	23
PT-VMZ50	19	PT-VZ570	23
PT-VMZ51	19	PT-VZ575N	23
PT-VMZ51S	19	PT-VZ580	22
PT-VMZ60	19	PT-VZ585N	22
PT-VMZ61	19	TH-D10000	14
PT-VMZ71	19	TH-DW10000	14
PT-VW330	26		
PT-VW340	23		
PT-VW345N	23		
PT-VW350	23		
PT-VW355N	23		
PT-VW360	23		
PT-VW430	24		
PT-VW431D	25		
PT-VW435N	24		
PT-VW440	24		
PT-VW530	23		
PT-VW535N	23		
PT-VW540	22		
PT-VW545N	22		
PT-VX400	26		
PT-VX400NT	26		
PT-VX405	24		
PT-VX406	23		
PT-VX41	26		
PT-VX410	23		
PT-VX415N	23		
PT-VX42	23		

The software is not compatible with any device models that are not listed in "List of models".

PT-RQ50K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/X/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	×
	Communication rate (bps)	×
	Parity	×
	Projector ID	×
Power state	Power on	×
	Standby	○
	During cooling	×
	During power on process	×
Security password setting	On and standby state	—
	On and during display of password input screen immediately after power on	—
	On and following password input immediately after power on	—

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 2048 X 1080	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-RQ35K / PT-RZ34K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1200	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-FRQ60

PT-FRQ50

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/T/(blank), cabinet color: B/W)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1080	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-RCQ10 / PT-RCQ80

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/J/X/(blank), lens: L/(blank), cabinet color: B/W)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	×
	Communication rate (bps)	×
	Parity	×
	Projector ID	×
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	—
	On and during display of password input screen immediately after power on	—
	On and following password input immediately after power on	—

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1200	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-RQ32K / PT-RZ31K / PT-RS30K
 ■ PT-RQ13K
 ■ PT-RQ22K / PT-RZ21K / PT-RS20K
 ■ PT-RZ12K / PT-RS11K
 ■ PT-RZ16K
 ■ PT-RZ990 / PT-RZ890 / PT-RZ790 / PT-RZ690
 ■ PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620
 ■ PT-RZ670 / PT-RW630
 ■ PT-FRZ60 / PT-FRZ50 / PT-FRZ55
 ■ PT-RZ575 / PT-RZ570
 ■ PT-DZ21K2 / PT-DS20K2 / PT-DW17K2 / PT-DZ16K2
 ■ PT-DZ21K / PT-DS20K / PT-DW17K / PT-DZ16K
 ■ PT-DZ13K / PT-DS12K / PT-DW11K / PT-DZ10K
 ■ PT-DZ870 / PT-DW830 / PT-DX100
 ■ PT-DZ780 / PT-DW750 / PT-DX820
 ■ PT-MZ16K / PT-MZ13K / PT-MZ10K
 ■ PT-MZ880 / PT-MZ780 / PT-MZ680
 ■ PT-MZ770 / PT-MW730 / PT-MZ670 / PT-MW630 / PT-MZ570 / PT-MW530

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/E/J/T/U/X/(blank), lens: L/(blank), cabinet color: B/K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-RZ475
PT-RZ470 / PT-RW430
PT-RZ370 / PT-RW330

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank), cabinet color: K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	×	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-DZ12000 / PT-D12000 / PT-DW100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	○	
	Standby	○	Transfer operations using a LAN connection cannot be performed if network standby is OFF.
	During cooling	○	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	○	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-DZ8700 / PT-DS8500 / PT-DW8300 / PT-DZ110XE / PT-DS100XE / PT-DW90XE / PT-DW105XEA

■ PT-DZ770 / PT-DW740 / PT-DX810

■ PT-DZ680 / PT-DW640 / PT-DX610

■ PT-DZ6710 / PT-DZ6700 / PT-DW6300 / PT-D6000 / PT-D5000

■ PT-DW730 / PT-DX800

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank), cabinet color: S/K/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×*1	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: Only the PT-DZ110XE, PT-DS100XE, PT-DW90XE, PT-DW105XEA, PT-DZ770, PT-DW740 and PT-DX810 support LAN connection.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-DZ570 / PT-DW530 / PT-DX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ TH-DW10000 / TH-D10000 / PT-DW10000 / PT-D10000

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	○
	Standby	○
	During cooling	○
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	○

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-D5700 / PT-D4000 / PT-DW5100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-LB426 / PT-LB386 / PT-LB356 / PT-LW376 / PT-LW336

■ PT-TW381R / PT-TW380 / PT-TX440 / PT-TX350

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/T/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	X
	Standby	○ (Standby mode: Normal)
	During cooling	X
	During power on process	X
Security password setting	On and standby state	X
	On and during display of password input screen immediately after power on	X
	On and following password input immediately after power on	X

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	X	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	X	
Display position	Display at any position	X	

*1: Background color can be set only for the PT-LW376, PT-LW336, PT-TW381R and PT-TW380.

PT-LB306

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: (blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-EZ770 / PT-EW730 / PT-EX800

■ PT-EZ580 / PT-EW640 / PT-EX610 / PT-EW540 / PT-EX510

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/Z/T/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×*1
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: Only the PT-EZ770, PT-EW730, and PT-EX800 support LAN connection.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

- PT-EZ590 / PT-EW650 / PT-EW550 / PT-EX620 / PT-EX520 / PT-EZ57
- PT-EZ591 / PT-EW651 / PT-EW551 / PT-EX621 / PT-EX521
- PT-FZ570 / PT-FW530 / PT-FX500
- PT-VMZ71 / PT-VMZ61 / PT-VMZ51 / PT-VMZ51S / PT-VMZ41 / PT-VMW61 / PT-VMW51
- PT-VMZ60 / PT-VMZ50 / PT-VMZ40 / PT-VMW60 / PT-VMW50

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/J/K/T/(blank), lens: L/(blank), cabinet color: B/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ590, PT-EW650, PT-EW550, PT-EZ57, PT-EZ591, PT-EW651, PT-EW551, PT-FZ570, PT-FW530, PT-VMZ71, PT-VMZ61, PT-VMZ51, PT-VMZ51S, PT-VMZ41, PT-VMW61, PT-VMW51, PT-VMZ60, PT-VMZ50, PT-VMZ40, PT-VMW60 and PT-VMW50.

■ PT-EZ570 / PT-EW630 / PT-EX600 / PT-EW530 / PT-EX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal, Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ570, PT-EW630 and PT-EW530.

PT-EX16K
PT-EX12K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-VZ585N / PT-VW545N / PT-VX615N

PT-VZ580 / PT-VW540 / PT-VX610 / PT-VX61 / PT-VX51

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/K/K1/T/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	X
	Standby	○ (Standby mode: Normal)
	During cooling	X
	During power on process	X
Security password setting	On and standby state	X
	On and during display of password input screen immediately after power on	X
	On and following password input immediately after power on	X

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

- PT-VZ575N / PT-VW535N / PT-VX605N
- PT-VZ570 / PT-VW530 / PT-VX600 / PT-VX406 / PT-VX46 / PT-VX60 / PT-VX50
- PT-VZ470
- PT-VW360 / PT-VX430
- PT-VW355N / PT-VX425N
- PT-VW350 / PT-VX420 / PT-VX421
- PT-VW345N / PT-VX415N
- PT-VW340 / PT-VX410 / PT-VX42

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/EA/J/T/Z/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	× ^{*1}
	Serial connection	○
	Communication rate (bps)	9600 ^{*2}
	Parity	NONE ^{*2}
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: Only the PT-VX406, PT-VX46, PT-VW360 and PT-VX430 support LAN connection.

*2: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○ ^{*1}	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VZ575N, PT-VW535N, PT-VZ570, PT-VW530, PT-VZ470, PT-VW360, PT-VW355N, PT-VW350, PT-VW345N and PT-VW340.

■ PT-VW440 / PT-VX510

■ PT-VW435N / PT-VX505N / PT-VW430 / PT-VX501 / PT-VX500 / PT-VX405 / PT-VX45

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/EP/KEA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×*1	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *2	
	Projector ID	— *2	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: Only the PT-VX405 and PT-VX45 support LAN connection.

*2: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW440, PT-VW435N and PT-VW430.

PT-VW431D

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Network)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-VW330 / PT-VX400NT / PT-VX400
PT-VX41

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW330.

PT-FW430 / PT-FX400

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-SW280A / PT-SX320A / PT-SX300A

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-SW280A.

PT-LZ370

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-LW25H / PT-LX30H / PT-LX26H / PT-LX26 / PT-LX22
PT-TW231R / PT-TW230

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-LW25H, PT-TW231R and PT-TW230.

PT-LB90NT

PT-LB3 / PT-LB2V / PT-LB2 / PT-LB1V / PT-LB1 / PT-ST10

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-LB90 / PT-LB78V / PT-LB75V

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	