



## Revitalize Sustainability and Image Quality in Classrooms and the Workplace

### PT-MZ782

The Series features PT-MZ882 (8,200 lm11), PT-MZ782 (7,500 lm11), and PT-MZ682 (6,500 lm) WUXGA models with a refined Multi-Laser Drive Engine for the optimal balance of high brightness, vivid colour, and low-maintenance operation. \*1 Measurement, measuring conditions, and method of notation are all compliant with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.

#### Key Features

Eco-Conscious Design Includes Recycled Materials

Bright and Sharp for Comfortable Visibility

A Streamlined Work/low and Efficient UX



PT-MZ782

<https://eu.connect.panasonic.com/gb/en/products/projectors/pt-mz782>

<b>Panel Size</b>	19.3 mm (0.76 in) diagonal (16:10 aspect ratio)
<b>Display Method</b>	Transparent LCD panel (x 3, R/G/B)
<b>LCD Panel</b>	
<b>Projector type</b>	LCD projectors
<b>Drive Method</b>	Active matrix
<b>Pixels</b>	2,304,000 (1920 x 1200) pixels x 3
<b>Light Source</b>	Laser diodes
<b>Light output 1, 2</b>	7,500 lm
<b>Time until light output declines to 50 %<sup>3</sup></b>	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)
<b>Resolution</b>	WUXGA (1920 x 1200 pixels)
<b>Contrast ratio 2</b>	3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1] or [2]. HDMI™ signal input)
<b>Lens</b>	
	Powered zoom (throw ratio 1.61–2.76:1), powered focus F = 1.7–2.3, f = 26.8–45.5 mm (for supplied lens; optional lenses also available)
<b>Screen Size (Diagonal)</b>	1.02–10.16 m (40–400 in), 1.52–10.16 m (60–400 in) with the ET-ELW22, 2.54–10.16 m (100–400 in) with the ET-ELU20, 16:10 aspect ratio
<b>Center-to-corner zone ratio<sup>2</sup></b>	85 %
<b>Lens shift Vertical (From the origin point of the lens mounter)</b>	±67 % (powered), ±60 % (with ET-ELW22), ±50 % (with ET-ELU20) (TBD)
<b>Keystone Correction Range</b>	Vertical: ±25 ° (±22 ° with ET-ELW21/ET-ELW22); (±25 ° with ET-ELW20/ET-ELT22/ET-ELT23); (±5 ° with ET-ELU20), Horizontal: ±30 ° (±15 ° with ET-ELW21/ET-ELW22); (±30 ° with ET-ELW20/ET-ELT22/ET-ELT23); (0 ° with ET-ELU20)
<b>Installation</b>	
	Ceiling/floor, front/rear, free 360-degree installation
<b>Lens shift Horizontal (From the origin point of the lens mounter)</b>	±35 % (powered), ±30 % (with ET-ELW22), ±24 % (with ET-ELU20) (TBD)
<b>Audio In</b>	M3 stereo mini-jack x 1
<b>Monitor Out</b>	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
<b>Remote 1 In</b>	M3 stereo mini-jack x 1 for wired remote control
<b>Remote 2 In</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals</b>	
<b>Computer In</b>	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
<b>MULTI SYNC OUT</b>	D-sub 9-pin (male) x 1 for link control
<b>HDMI™ IN</b>	HDMI™ x 3 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input <sup>4</sup> ), CEC supported
<b>SERIAL/MULTI SYNC IN</b>	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
<b>LAN</b>	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)
<b>DC Out</b>	USB Type A x 1 (for power supply, DC 5 V, 2 A)
<b>Audio Out</b>	M3 stereo mini-jack x 1
<b>DIGITAL LINK/LAN</b>	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p <sup>4</sup> , 5 signal input)
<b>Power Supply</b>	
	AC 100–240 V, 50 Hz/60 Hz
<b>NORMAL</b>	385 W (AC 100–120 V), 365 W (AC 200–240 V) (TBD)
<b>ECO</b>	280 W (AC 100–120 V), 270 W (AC 200–240 V) (TBD)
<b>QUIET</b>	275 W (AC 100–120 V), 265 W (AC 200–240 V) (TBD)
<b>Maximum power consumption 6</b>	428 W (4.7–2.3 A) (450 VA) (Power consumption is 408 W at AC 200–240 V) (TBD)
<b>On-mode power consumption (Operating mode) 6</b>	
<b>Dimensions (W x H x D)</b>	561 x 224 x 439 mm (22 3/32" x 8 13/16" x 17 9/32") (With legs at shortest position, including lens and protruding parts)
<b>Operating Environment</b>	
	Operating temperature: 0–45 °C (32–113 °F) <sup>8</sup> , operating humidity: 10–80 % (no condensation)
<b>Cabinet Materials</b>	
	Molded plastic
<b>Applicable Software</b>	
	Logo Transfer Software, Multi Monitoring & Control Software, Smart Projector Control for iOS/Android™, Geometry Manager Pro 9
<b>Filter</b>	
	Included (Estimated maintenance time: approx. 20,000 hours)
<b>Operation noise 2</b>	33 dB (NORMAL/ECO), 27 dB (QUIET) (TBD)
<b>Weight 7</b>	Approx. 18.6 kg (41.0 lbs) (with supplied lens)
<b>Notification</b>	Please note for internal use only until the official product release.